

KL80TSX

Prime - 65 kW Standby - 72 kW

ENERMAX SERIES



TecnoGen's Enermax Series generator is built for reliability and is ideal for continuous heavy duty applications.

This series ranges in size from 25 kW to 1000kW and is equipped with market leading engines - Volvo, FPT, Kohler. Standard features include Deep Sea controller, camlocks, block heater, battery charger and external fuel connect.





KL80TSX SPECIFICATIONS

GENERATOR SPECS	
PRIME (kW)	65
STANDBY (kW)	72
RPM	1800
VOLTAGE 1PH	240/120V
VOLTAGE 3PH	480/277V 208/120V
FREQUENCY (Hz)	60
CONTROLLER BRAND	Deep Sea
CONTROLLER MODEL	DSE7310
ALTERNATOR MAKE	Leroy Somer
ALTERNATOR MODEL	LSA 44.3S3
SYSTEM VOLTAGE	12V
SOUND LEVEL @ 23 FEET	69
AMPS	09
SINGLE PHASE 120V zz (P.F. 0,8)	217 X 2 zz
SINGLE PHASE 240V (P.F. 0,8)	217
THREE PHASE 208V (P.F. 0,8)	226
THREE PHASE 240V (P.F. 0,8)	195
THREE PHASE 480V (P.F. 0,8)	98
ENGINE SPECS	30
	Kohler
MAKE	Kohler KDI3404TCR
MAKE MODEL	KDI3404TCR
MAKE MODEL EPA LEVEL	KDI3404TCR Tler 4F
MAKE MODEL EPA LEVEL CYLINDERS	KDI3404TCR Tler 4F 4
MAKE MODEL EPA LEVEL CYLINDERS GROSS HP	KDI3404TCR Tler 4F
MAKE MODEL EPA LEVEL CYLINDERS GROSS HP EXTERNAL FUEL VALVE	KDI3404TCR Tler 4F 4 100 YES
MAKE MODEL EPA LEVEL CYLINDERS GROSS HP EXTERNAL FUEL VALVE FUEL CONTAINMENT	KDI3404TCR Tler 4F 4 100
MAKE MODEL EPA LEVEL CYLINDERS GROSS HP EXTERNAL FUEL VALVE FUEL CONTAINMENT FUEL CONSUMPTION	KDI3404TCR Tler 4F 4 100 YES
MAKE MODEL EPA LEVEL CYLINDERS GROSS HP EXTERNAL FUEL VALVE FUEL CONTAINMENT FUEL CONSUMPTION FUEL CAPACITY (Gallons)	KDI3404TCR Tler 4F 4 100 YES 110%
MAKE MODEL EPA LEVEL CYLINDERS GROSS HP EXTERNAL FUEL VALVE FUEL CONTAINMENT FUEL CONSUMPTION FUEL CAPACITY (Gallons) 75%	KDI3404TCR Tler 4F 4 100 YES 110%
MAKE MODEL EPA LEVEL CYLINDERS GROSS HP EXTERNAL FUEL VALVE FUEL CONTAINMENT FUEL CONSUMPTION FUEL CAPACITY (Gallons)	KDI3404TCR TIer 4F 4 100 YES 110% 92 3.28 gal/h
MAKE MODEL EPA LEVEL CYLINDERS GROSS HP EXTERNAL FUEL VALVE FUEL CONTAINMENT FUEL CONSUMPTION FUEL CAPACITY (Gallons) 75% RUN TIME @ 75% DEF	KDI3404TCR TIer 4F 4 100 YES 110% 92 3.28 gal/h
MAKE MODEL EPA LEVEL CYLINDERS GROSS HP EXTERNAL FUEL VALVE FUEL CONTAINMENT FUEL CONSUMPTION FUEL CAPACITY (Gallons) 75% RUN TIME @ 75%	KDI3404TCR TIer 4F 4 100 YES 110% 92 3.28 gal/h 28
MAKE MODEL EPA LEVEL CYLINDERS GROSS HP EXTERNAL FUEL VALVE FUEL CONTAINMENT FUEL CONSUMPTION FUEL CAPACITY (Gallons) 75% RUN TIME @ 75% DEF DEF TANK CAPACITY (Gallons) WEIGHTS AND DIMENSIONS	KDI3404TCR TIer 4F 4 100 YES 110% 92 3.28 gal/h 28
MAKE MODEL EPA LEVEL CYLINDERS GROSS HP EXTERNAL FUEL VALVE FUEL CONTAINMENT FUEL CONSUMPTION FUEL CAPACITY (Gallons) 75% RUN TIME @ 75% DEF DEF TANK CAPACITY (Gallons) WEIGHTS AND DIMENSIONS SKID W/O TRAILER	KDI3404TCR TIer 4F 4 100 YES 110% 92 3.28 gal/h 28
MAKE MODEL EPA LEVEL CYLINDERS GROSS HP EXTERNAL FUEL VALVE FUEL CONTAINMENT FUEL CONSUMPTION FUEL CAPACITY (Gallons) 75% RUN TIME @ 75% DEF DEF TANK CAPACITY (Gallons) WEIGHTS AND DIMENSIONS	KDI3404TCR TIer 4F 4 100 YES 110% 92 3.28 gal/h 28 4.23
MAKE MODEL EPA LEVEL CYLINDERS GROSS HP EXTERNAL FUEL VALVE FUEL CONTAINMENT FUEL CONSUMPTION FUEL CAPACITY (Gallons) 75% RUN TIME @ 75% DEF DEF TANK CAPACITY (Gallons) WEIGHTS AND DIMENSIONS SKID W/O TRAILER Dry WEIGHT (lbs.)	KDI3404TCR TIer 4F 4 100 YES 110% 92 3.28 gal/h 28 4.23
MAKE MODEL EPA LEVEL CYLINDERS GROSS HP EXTERNAL FUEL VALVE FUEL CONTAINMENT FUEL CONSUMPTION FUEL CAPACITY (Gallons) 75% RUN TIME @ 75% DEF DEF TANK CAPACITY (Gallons) WEIGHTS AND DIMENSIONS SKID W/O TRAILER Dry WEIGHT (lbs.) Wet WEIGHT (lbs.) LENGTH (in.)	KDI3404TCR TIER 4F 4 100 YES 110% 92 3.28 gal/h 28 4.23 4.23
MAKE MODEL EPA LEVEL CYLINDERS GROSS HP EXTERNAL FUEL VALVE FUEL CONTAINMENT FUEL CONSUMPTION FUEL CAPACITY (Gallons) 75% RUN TIME @ 75% DEF DEF TANK CAPACITY (Gallons) WEIGHTS AND DIMENSIONS SKID W/O TRAILER Dry WEIGHT (lbs.)	KDI3404TCR TIer 4F 4 100 YES 110% 92 3.28 gal/h 28 4.23 3950 4631 100



TecnoGen's 80kVA generator uses the Kohler engine coupled to an industry standard Leroy Somer alternator producing 65kW of prime power. Standard features include camlocks, block heater and battery charger. The Deep Sea controller makes retrieving vital stats like fuel levels, run time and start logs easy and the sealed doors and 2" thick insulation throughout gives this gen a 69 dBA rating.

The internal fuel capacity is 92 gallons allowing for a run time of up to 28 hours @ 75% load. The convenient external fuel hookup allows for quick connect to an additional fuel cell if needed. The TecnoGen Enermax series is built for reliability and is ideal for continuous heavy-duty applications. Available on trailer or skid mounted.









